DEHUMIDIFIER

MODEL DD45



LCD ELECTRONIC CONTROLS

CHOOSE THE IDEAL HUMIDITY LEVEL BY ADJUSTING THE HUMIDISTAT. THE ELECTRONIC CONTROLS ALLOW YOU TO MONITOR RELATIVE HUMIDITY AND TEMPERATURE.



VISIBLE WATER LEVEL

WITH ITS FRONTALLY LOCATED TANK AND TRANSPARENT WATER LEVEL WINDOW, YOU CAN EASILY SEE HOW MUCH WATER HAS BEEN COLLECTED.

TANK OR DRAINAGE HOSE

COLLECTED WATER CAN EITHER BE DRAINED PASSIVELY OUT OF THE UNIT WITH THE 3' PROVIDED HOSE, OR THE USER CAN MANUALLY EMPTY THE COLLECTION TANK.



DeLonghi

1	il
1	No. of Concession, Name

SAP:	0148840203				
UPC:	0-44387-00045-1		1500		
SCC14:			vv	Wattage:	
	w	D	Н	Lbs	-
Unit	14.96	11.81	24.02	41.23	
VOL Unit f	it3:	2.46			
Carton:	16.54	13.98	27.17	47.84	
VOL Carto	n ft3:	3.63			
Pcs per Ma	eter:	0			
Master:	0.00	0.00	0.00	0.00	
VOL Maste	er ft3:	0.00			
Container:	20'	40'	40H C'	45'	
	255	534	534	0	
Factory cod	le: NWT				

ELECTRONIC CLIMATE CONTROL WITH LCD DISPLAY

- ADJUSTABLE HUMIDISTAT
- ROOM THERMOSTAT
- 24-H TIMER
- ANTI-FROST DEVICE (DOWN TO 41°F)
- FAN SPEED CONTROL 2 FAN SPEEDS

TANK CONTROL SYSTEM WITH ALARM

CAN BE EASILY MOVED BY CASTOR WHEELS AND HANDLES

R410A REFRIGERANT GAS



UPDATED: 11/24/09

DISCLAIMER: FEATURES AND COLORS ARE TENTATIVE AND SUBJECT TO CHANGE WITHOUT NOTICE.